



**Product Code:**

F6U600au

**Description:**

600VA Line Interactive UPS with AVR

**UPC:**

722868849804

**Overview:**

The 600VA Line Interactive UPS provides up to 20 minutes battery backup time and if a power outage is detected, the included software will automatically shutdown your computer safely. Featuring Automatic Voltage Regulation and advanced surge protection ensures smooth consistent power to your connected equipment.

Belkin's Connected Equipment Warranty will repair or replace any equipment damaged by a surge, spike, or lightning strike while properly connected to a Belkin Line Interactive UPS, up to \$50,000.

**Features:**

- Automatic Voltage Regulation: Ensures smooth consistent power to the connected equipment.
- Connected Equipment Warranty: Belkin will repair or replace any equipment damaged by a surge, spike, or lightning strike while properly connected to a Belkin Line Interactive UPS, up to \$50,000.
- 3-Year Product Warranty: Belkin will replace, free of charge, any Belkin Line Interactive UPS that is defective or expires after protecting your electronic devices. There is no limit to the number of times Belkin will replace the expired Line Interactive UPS during the warranty period.
- 3 battery backup with surge protection sockets and 1 surge protected only socket.
- RJ11 surge protected port for telephone/modem.
- Certified to all Australian and New Zealand safety standards.
- Automatic power management shutdown software. Includes the ability to safely shutdown the attached computer and automatically save open files during power failure, scheduled shutdowns, diagnostic support, printable logs and history, visual metres & graphs
- USB port for plug-and-play communication.

**Package Includes:**

- 600VA Line Interactive UPS
- USB Cable
- 1 x 1.5m Input Power Cable
- 2 x 1.5m IEC to IEC Output Cables
- Automatic Power Management Software (CD)
- Quick installation guide
- Hassle Free Connected Equipment Warranty sheet

### Specifications:

- Battery Load Capacity: 600VA (360W)
- Battery Backup Sockets: 3
- Surge-Protected Sockets: 1
- Communication Interface: USB
- Telephone: RJ11 – 1 In/1 Out
- Input Power Cable: 1.5m with insulated pins
- Output Power Cable: 2 x 1.5m IEC to IEC
- Typical Battery Recharge Time: 6 hrs. to 90%
- Typical Battery Life: 2-4 yrs
- Battery Output Voltage: 230Vac-240Vac
- Battery Output Frequency: 50Hz/60Hz
- Battery Output Waveform: Modified Sinewave
- Product Dimensions: 330mm x 100mm x 140mm
- Product Weight: 5.2kg
- Software: Supports Windows 98/2000/ME/XP/ Vista/7 (x32 & x64), Mac OS 10.x, Linux

### Images:

[Belkin Image Database Link](#)

