

XMP-6400

1080p Live TV + Signage Media Player



Turn the Entertainment Only TV into Advertisable Medium

XMP-6400 is world's first open standard HDMI-in media player. It easily converts the already installed sports TV into multi-purpose digital signage screen. Mix the in store promotion and event message along with sport's channel, customers will experience non-stopping sports game just like before and store owner can freely switch screen back and forth from full screen to multiple zone to add some store promotion or ticker message.



Technical Specification

Open Standards Supported

- HTML5, JavaScript, and CSS
- Android 4.4 API
- W3C SMIL for cross-platform management
- W3C Widgets for HTML delivery
- POPAI Digital Signage Content Standards, including:
 - S1 (JPEG 480p baseline)
 - S2 (JPEG 720p baseline)
 - S4 (MPEG L2 audio)
 - S5 (MP3 audio, 384Kbps)
 - S6 (MPEG-1 SIF, 3Mbps CBR)
 - S7 (MPEG-1 480p, 10Mbps CBR)
 - S8 (MPEG-1 720p, 15Mbps CBR)
 - S9 (MPEG-2 480p, 6Mbps CBR)
 - S10 (MPEG-2 720p, 12Mbps CBR)
 - S11 (H.264/MPEG-4 AVC, 480p, 6Mbps CBR)
 - S12 (H.264/MPEG-4 AVC, 720p, 10Mbps CBR)
 - E1 (PNG 24bpp+alpha, 480p)
 - E2 (PNG 24bpp+alpha, 720p)
 - E4 (VC-1/WMV9, MP@ML, 720p)
 - E7 (MPEG-4 ASP, 480p, 10Mbps CBR)
 - E8 (H.264/MPEG-4 AVC, 1080p, 20Mbps CBR)

Advanced Signage Features

- Remote commissioning
- AlwaysOn, AppLock to prevent unauthorized access
- StrongCache for continued playback even when network is not available
- Multi-zone screen layout, transparent PNG overlay, and graphical scrolling ticker
- Automatic error recovery with built-in WDT

HTML5 Support

- Widgets for calendar, clock, news, weather, and web page integration
- HTML5 technologies including CSS and Javascript
- WebKit-based browser engine, same as Google Chrome™ and Apple Safari® browsers

Content Management

- SignApps Express utility
- 3rd party solution (optional license)

Connectivity

- WiFi: 802.11 b/g/n (2.4 GHz)
- HDMI 1.4 output (Full-HD 1080p with audio)
- VGA out
- Ethernet 10/100 BASE-T
- USB 2.0 x 3
- HDMI 1.4 input with HDCP (HD 720p with audio)
- 3.5mm analog stereo audio out
- S/PDIF out
- RS-232
- Micro USB for ADB
- Optional 3G/4G mobile module via USB
- AniBeacon™ (BLE)

Local Storage

- 8 GB eMMC built-in (approx. 360 minutes of typical 720p video @3 Mbps)
- Micro SD card slot (support up to 32GB storage)

Mounting kit

- Built-in wall mount bracket

Supplied accessories

- HDMI cable
- External 2dB Wi-Fi antenna
- Velcro
- Power/Micro SD card brackets

Expansion Options

- 16GB/32GB micro SD/SDHC memory card

AC Adapter

- Input: 100-240V, 50-60 Hz, 0.5A Max.
- Output: 12V, 1.5A
- UL/CB/PSE certified power supplies
- Interchangeable connector system includes US plugs (Option for EU, UK and AUS plugs)

Environmental

- Operating temperature: 0 to 50°C
- Humidity: 10 to 85% @ 40°C, non-condensing

Dimensions for Product and Package

- Size: 138.60mm x 128.10mm x 30.20mm / 5.45" x 5.04" x 1.19"
- Weight: 366 g / 0.8 lbs.
- Individual Package Size: 226mm x 172mm x 89 mm / 8.89" x 6.77" x 3.5"
- Outer Carton Size: 482mm x 390mm x 245mm / 18.97" x 15.35" x 9.64"
- Units per Outer Carton: 10

Certifications

- CE/FCC/IC

Warranty

- 1-year limited parts & labor

Product Photos



Sports bar advertisement TV demo
(Monitor not included)

Contact

IAdea Corporation (Headquarters)
 3F, No. 21, Lane 168, Xingshan Road
 Taipei, Taiwan 114
 Phone: +886-2-2791-1110
 Fax: +886-2-2791-1170
 Email: Sales@IAdea.com
 Website: <http://www.IAdea.com>

IAdeaAmerica Corp.
 20 Fairbanks, Suite 170
 Irvine, CA 92618
 Tel: +1-949-305-6489
 Email: US-Sales@IAdea.com

Authorized Reseller

